

4033A

1x15 Pulse Distribution Amplifier 5V Output



4033A 1x15 Pulse Distribution Amplifier 5V Output

Key Features

- Detects 1PPS, IRIG-B, or other
- Compact rack mount 1U-high package
- ± 500 ps differential delay between outputs
- LED status indicators for all inputs and outputs
- Status information via Ethernet

The Microsemi® 4033A is a one-input, fifteen-output pulse distribution amplifier in a 1U, 19-inch rack mount chassis. It provides fifteen isolated outputs from a single input. An Ethernet port on the rear panel provides the capability to remotely monitor the status of the input and all output signals. Any failure in the unit will immediately provide an alarm to the Ethernet port. The front panel provides green LED status for the input and green/red for all output signals, as well as indicating an input of 1PPS, DC IRIG, or Other.

4033A

Specifications

ELECTRICAL SPECIFICATIONS

- 1PPS Output (15)
 - Output impedance: 50 \pm 5 Ω
 - Load impedance: 50 Ω
 - Logic one: 4.5 V minimum
 - Logic zero: +0.8 V maximum
 - Rise time: <2.0 ns
 - Fall time: <2.0 ns
 - Jitter: <50 ps rms
 - Skew between outputs: < \pm 2 ns
 - Connectors: BNC female
- 1PPS Input
 - Repetition rate: 1PPS – 1MPPS
 - Duty cycle: 0 – 50%
 - Input impedance: 50 Ω
 - Logic one: >2.4 V
 - Logic zero: +0.8 V maximum
 - Connector: BNC female
- Status
 - Senses signal presence on all inputs and outputs
 - Green/Red LEDs on Front Panel
 - LED Indicators for 1PPS, DC IRIG, and Other
 - Network (RJ-45 connector)

ENVIRONMENTAL & PHYSICAL SPECIFICATIONS

- Temperature: 0°C to 50°C
- Humidity: 0 to 95% non-condensing
- AC Input: 90 – 264 V AC, 10 W, 47 – 63 Hz
- Dimensions: 1.75" (4.44 cm) H x 19" (48.26 cm) W x 12" (30.48 cm) D
- Weight: 9 lb (4 kg)



Rear view



Microsemi.

Microsemi Corporate Headquarters
 One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 (949) 380-6100
 Sales: +1 (949) 380-6136
 Fax: +1 (949) 215-4996

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor solutions for aerospace, defense and security; enterprise and communications; and industrial and alternative energy markets. Products include high-performance, high-reliability analog and RF devices, mixed signals and RF integrated circuits, customizable SoCs, FPGAs, and complete subsystems. Microsemi is headquartered in Aliso Viejo, Calif. Learn more at www.microsemi.com

©2014 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

DS/4033A/060314 900 00528 000B